Proxima DP5610 Projector Technical and Functional Specifications

What's included:	Infrared remote control with mouse control
	Universal I.E.C. power cord (U.S., and Europe)
	Product documentation
	• Lens cap
	Two AA batteries
	VGA video cable
	• RS-232 cable
	Macintosh video adapter cable
	Composite video/audio cable
	Computer audio cable
Computer Compatibility:	BM PC, PS/2, Pentium and compatibles
	Apple Macintosh, Power Macintosh, PowerBook and compatibles
Video Compatibility:	NTSC & NTSC 4.43 MHz, PAL, SECAM
Input Sources	• 2 computer inputs (Mac and/or PC)
	• 2 video inputs
	4 stereo audio inputs
Resolution:	• 832 x 624 pixels
Resolutions Supported:	• VGA (640 x 480)
	• SVGA (800 x 600)
	• Mac (832 x 624)
	• XGA (1024 x 768, compressed)
Keystone Correction:	• 10.0 degrees
Number of Colors:	• 16.7 million
Projection Distance:	• 3.6ft (1.1m) to 75.6ft (23.0m) from screen
Contrast Ratio:	• 100:1 (typical)
Brightness:	500 ANSI lumens (typical)
Lamp:	Metal Halide, 250 watt
	"Replace Lamp" indicator light
Lamp life:	1,000 hours to 50% brightness
Dimensions:	• 11.6 " (W) x 18.1" (L) x 5.9" (H)
	• 29.6 cm (W) x 45.9 (L) cm x 14.9 cm (H)
Weight:	• 16.5 lb. (7.5 kg)
Projection Zoom Lens:	 Projection (Zoom) Lens: f/2.5 (wide) to f/3.2 (telephoto) motorized zoom and focus, 1.77 in. to 2.95 in. (44.9 mm to 74.9 mm) focal length
Image Size (Diagonal):	• Adjustable from 20" to 33.3' (.7.8 m to 10.2 m)
Remote Control:	Including zoom and focus control, mouse control
Audio:	Internal monitor speaker
	Audio following video switching
	Line-level stereo audio cut
Power Requirements:	• Auto switching 100 - 120 VAC, 200 - 265 VAC
Power Consumption:	• 5.0/3.0A (Max Amperes); 360 watts
Operating Temp. (Sea Level):	• 40F (5C) to 85F (35C)
Approvals:	FCC Class A, UL, cUL,CE and TUV
Warranty:	One year on projector parts and labor. (excluding lamp)

Copyright @ 1997-2004 InFocus Corporation. All Rights Reserved.